

NEW



LAN, USB3.0*2, VGA, RS232,
USB2.0*2, DC Jack, Kensington Lock



Docking with Battery Charger



Protection Jacket with Handstrap and Stylus Pen(MPP1.51)



Features

- Intel® Apollo lake Pentium N4200
- 1 x DDR3L SO-DIMM slot Up to 8GB
- 10.1" 1280 x 800 w/Pcap touch +MPP1.51 pen solution
- 2 x USB 3.0 , 1 x Micro HDMI , 1 Audio combo jack , 1 x RJ-45 LAN
- 1 x Smart card reader, 1 x SD card reader
- 2M Pixel front camera, 5M Pixel rear camera
- Option for Office Docking I/O : 2 x USB 3.0, 2 x USB 2.0, 1 x LAN , 1 x VGA , 1 X RS232 (Option for NFC, Barcode Scanner)
- DC-IN 12~24V
- Accessories (Option) : Protection cover, VESA mount , Active Pen
- Detachable Battery design

Specifications

Key features	Dimension	279 x 192.5 x 17.9 mm
	Weight	990g
	Display	10 inch, 16:10 ratio
	Sealing	IP65
	Drop/Shock	MIL-STD-810G 4-feet drop
	Battery life	Up to 9 hours
	Operating Temp	0~40 degree
	Storage Temp	-20~60 degree
Specification	CPU	Intel Apollolake Pentium N4200
	System Memory	Default DDR3L 4GB. Max 8GB
	Storage	64GB (Min)/ 128GB (Max) M.2 3D TLC SSD
	Display	10.1" 1280 x 800 Projected Capacitive Touch Screen. Multi touch 10 points Microsoft pen protocol (MPP) supported
	Button	Power, Barcode Scanner
	Power	AC: support 100~240V DC: support 12/19/24V
	Audio	1w x 2, Stereo type Internal Microphone: Stereo (set with Camera module)
	Sensors	Light Sensor, E-Compass Sensor, G-Sensor, Gyro Sensor
	I/O ports	USB x2 (Ver.3.0) Headphone out x1 (headphone/microphone combo jack, 3.5Ø, iPhone Type) Power jack x 1(19V & 24V) Micro SD slot x1, SDXC type, (SD 4.0) SIM Slot Pogo pin: x1 RJ45: x1, Intel WGI211AT Micro HDMI (Output) x 1
	Battery	Battery 1 Li-Polymer, 41W/h, 5550mAh, Pack swappable Battery Life: over: 9 hrs
	Security	Kensington x1, TPM 2.0
	Wireless LAN + BT	802.11 ac/a/b/g/n, Intel 8260 , Ver4.2
	Camera	2M Pixel front camera w/ ALS and D-MIC *2 5M Pixel rear camera +Auto Focus
	Smart card reader	Support
Data collection	Option	NFC / Barcode scanner / LTE
	OS	Microsoft® Windows 10 IoT / Ubuntu
	Office Docking I/O	USB 3.0 x 2, USB 2.0 x 2, Power Jack x 1, LAN Port x1, POGO Pin x 1, VGA output x1, RS232 x 1
	Accessories Option	Protection cover Vesa mount Active Stylus Pen